NSN 5925-01-218-5419

Circuit Breaker - Page 1 of 2



Vi	iew Online at https://aerobasegroup.com/nsn/5925-01-218-5419
В	ody Style:
Si	ingle pole type
В	ody Length:
2.	500 inches
B	ody Width:
0.	750 inches
С	ase Material:
PI	lastic
C	enter To Center Distance Between Terminals Parallel To Length:
1.	680 inches
C	istance Between Centerlines Of Mounting Facilities Parallel To Body Length:
2.	060 inches
5	witch Contact Arrangement:
Si	ingle pole, double throw
B	oss Height:
).	115 inches
M	ounting Surface To Terminal End Distance:
2.	510 inches
2	ole Quantity:
Λ	lounting Facility Type And Quantity:
) -	threaded hole
51	torage Type:
3	eneral purpose warehouse
Г	hready Qty Per Inch (tpi):
32	2
M	aximum Continuous Load Current Rating Per Pole:
5.	0 amperes ac single location
o	perating Voltage Type And Rating Per Pole In Volts:
2!	50.0 ac single location
M	aximum Interrupting Capacity Current Type And Rating Per Pole In Amps:
1(000.0 ac single location
С	ircuit Protection Type:
0	vercurrent single location
٢ı	rip Release Method:
M	lagnetic single location
Tı	rip Release Characteristic:
Ti	ime delay single location
U	Itimate Trip Rating Of Continuous Current Rating Per Pole In Percent:
12	25.0 single location
R	eset Method:
	lanual

NSN 5925-01-218-5419

Circuit Breaker - Page 2 of 2



Main Contact Tripping Mechanism Type: Trip free Manual Actuator Type And Quantity: 1 toggle **Actuator Function:** Trip-reset **Actuator Position Designation:** At pole one **Auxiliary Switch Function And Quantity:** 1 alarm **Internal Trip Release Configuration:** Series trip single location Thread Size: 0.138 inches **Switch Location And Position Designation:** Internal at pole one Trip Delay Time In Seconds Per Rated Continuous Current: 2.275 at 200 pct and 10.000 at 200 pct single location Inclosure Protection Type For Which Designed: Fungus resistant Switch Terminal Type: Tab, solder lug Switch Current Rating And Type In Amps: 5.0 ac and 1.0 dc Switch Voltage Rating And Type In Volts: 125.0 ac and 60.0 dc **Frequency In Hertz:** 60.0 single location **Thread Series Designator:** Unc **Terminal Type And Quantity:** 2 threaded stud Shelf Life: N/a Unit Of Measure: --**Demilitarization:** No Fiig: A030a0