## NSN 5925-01-218-5420

Circuit Breaker - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5925-01-218-5420

| Body Style:   |
|---|
| Multipole-multiple actuator type  |
| Body Length:  |
| 3.000 inches  |
| Body Width:   |
| 2.230 inches  |
| Body Height:  |
| 2.580 inches  |
| Case Material:  |
| Plastic   |
| Center To Center Distance Between Terminals Parallel To Width:          |
| 0.740 inches  |
| Fragility Factor:   |
| Moderately rugged   |
| Boss Height:  |
| 0.250 inches  |
| Pole Quantity:  |
| 2   |
| Mounting Facility Type And Quantity:                                    |
| 4 terminal  |
| Storage Type:   |
| General purpose warehouse   |
| Special Handling Feature:   |
| Magnetic  |
| Maximum Continuous Load Current Rating Per Pole:                        |
| 25.0 amperes ac all locations   |
| Operating Voltage Type And Rating Per Pole In Volts:                    |
| 240.0 ac all locations  |
| Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps: |
| 10000.0 ac all locations  |
| Circuit Protection Type:  |
| Overcurrent all locations   |
| Trip Release Method:  |
| Thermal-magnetic all locations  |
| Trip Release Characteristic:  |
| Time delay all locations  |
| Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:  |
| 135.0 all locations   |
| Reset Method:   |
| Manual  |
| Main Contact Tripping Mechanism Type:                                   |

Trip free

## NSN 5925-01-218-5420

Circuit Breaker - Page 2 of 2



| Manual Actuator Type And Quantity:  |
|---|
| toggle  |
| Actuator Function:  |
| Frip-reset  |
| Actuator Position Designation:  |
| At pole two   |
| Trip Delay Time In Seconds Per Rated Continuous Current:  |
| 2.000 at 200 pct all locations  |
| nclosure Protection Type For Which Designed:  |
| Corrosion resistant   |
| Trip Release Ambient Tempurature Rating:  |
| 25.0 degrees celsius all locations  |
| Frequency In Hertz:   |
| 60.0 all locations  |
| Test Data Document:   |
| 31348-w-c-375 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format |
| excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental       |
| and performance requirements and test conditions that are shown as "typical", "average", "", etc.).   |
| Ferminal Type And Quantity:   |
| 2 clip and 2 compression  |
| Specification Data:   |
| 31348-w-c-375/2 government specification  |
| Shelf Life:   |
| N/a   |
| Jnit Of Measure:  |
| -   |
| Demilitarization:   |
| No  |
| Filg:   |
| A030a0  |
|   |
|   |
|   |