## NSN 5925-01-219-3488

Circuit Breaker - Page 1 of 2

**Body Style:** 



View Online at https://aerobasegroup.com/nsn/5925-01-219-3488

Multipole-multiple actuator type
Bushing Length:
0.125 inches
Body Length:
6.000 inches
Body Width:
2.750 inches
Case Material:
Plastic
Center To Center Distance Between Terminals Parallel To Length:
5.062 inches
Center To Center Distance Between Terminals Parallel To Width:
1.375 inches
Unthreaded Mounting Hole Diameter:
0.188 inches
Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:
4.500 inches
Fragility Factor:
Moderately rugged
Mounting Surface To Terminal End Distance:
3.375 inches
Pole Quantity:
2
Arc Quenching Method:
Magnetic blowout
Mounting Facility Type And Quantity:
2 unthreaded hole
Storage Type:
General purpose warehouse
Special Handling Feature:
Magnetic
Maximum Continuous Load Current Rating Per Pole:
30.0 amperes ac and 30.0 amperes dc all locations
Operating Voltage Type And Rating Per Pole In Volts:
240.0 ac and 250.0 dc all locations
Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:
10000.0 ac and 50000.0 dc all locations
Circuit Protection Type:
Overcurrent all locations
Trip Release Method:
Thermal-magnetic all locations

## **NSN 5925-01-219-3488** Circuit Breaker - Page 2 of 2



Trip Release Characteristic:
Time delay all locations
Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:
125.0 all locations
Reset Method:
Manual
Main Contact Tripping Mechanism Type:
Trip free
Manual Actuator Type And Quantity:
1 toggle
Actuator Function:
Trip-reset
Actuator Position Designation:
At pole two
Trip Delay Time In Seconds Per Rated Continuous Current:
35.000 at 200 pct and 120.000 at 200 pct all locations
Inclosure Protection Type For Which Designed:
Dustproof and general purpose and fungus resistant
Trip Release Ambient Tempurature Rating:
50.0 degrees celsius all locations
Frequency In Hertz:
60.0 all locations
Unpackaged Unit Weight:
3.000 pounds
Terminal Type And Quantity:
4 compression
Shelf Life:
N/a
Unit Of Measure:
<del>.</del>
Demilitarization:
No
Fiig:
A030a0