NSN 5925-01-222-0833

Circuit Breaker - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5925-01-222-0833

Body Style: Single pole type Mounting Slot Width: 0.178 inches **Body Length:** Between 5.790 inches and 5.810 inches **Body Width:** Between 1.016 inches and 1.036 inches **Case Material:** Plastic Center To Center Distance Between Terminals Parallel To Length: Between 3.537 inches and 3.557 inches **Unthreaded Mounting Hole Diameter:** 0.164 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Length: Between 2.740 inches and 2.760 inches **Fragility Factor:** Moderately rugged **Boss Height:** Between 0.209 inches and 0.229 inches Mounting Surface To Terminal End Distance: Between 3.229 inches and 3.249 inches **Pole Quantity:** 1 Arc Quenching Method: Magnetic blowout Mounting Facility Type And Quantity: 2 threaded hole and 1 unthreaded hole and 1 slot Storage Type: General purpose warehouse Thready Qty Per Inch (tpi): 32 Maximum Continuous Load Current Rating Per Pole: 35.0 amperes dc single location **Operating Voltage Type And Rating Per Pole In Volts:** 130.0 dc single location Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps: 1000.0 dc single location **Circuit Protection Type:** Overcurrent single location **Trip Release Method:** Magnetic-hydraulic single location

NSN 5925-01-222-0833

Circuit Breaker - Page 2 of 2



Trip Release Characteristic:

Time delay single location

Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:

125.0 single location

Reset Method:

Manual

Main Contact Tripping Mechanism Type:

Trip free

Manual Actuator Type And Quantity:

1 toggle

Actuator Function:

Trip-reset

Actuator Position Designation:

At pole one

Internal Trip Release Configuration:

Series trip single location

Thread Size:

0.138 inches

Trip Delay Time In Seconds Per Rated Continuous Current:

0.700 at 200 pct and 20.000 at 200 pct single location

Inclosure Protection Type For Which Designed:

General purpose

Thread Series Designator:

Unc

Terminal Type And Quantity:

2 threaded stud

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A030a0