

View Online at <https://aerobasegroup.com/nsn/5925-01-222-2250>

Body Style:

Rectangular dimensional envelope

Overall Length:

8.438 inches

Overall Height:

3.785 inches

Overall Width:

5.625 inches

Unthreaded Mounting Hole Diameter:

Between 0.203 inches and 0.438 inches

Fragility Factor:

Moderately rugged

Pole Quantity:

3

Arc Quenching Method:

Deion

Mounting Facility Type And Quantity:

5 unthreaded hole

Storage Type:

General purpose warehouse

Features Provided:

Adjustable trip release

Maximum Continuous Load Current Rating Per Pole:

225.0 amperes ac all locations

Operating Voltage Type And Rating Per Pole In Volts:

500.0 ac all locations

Circuit Protection Type:

Overcurrent all locations

Trip Release Method:

Thermal-magnetic all locations

Trip Release Characteristic:

Instantaneous and time delay all locations

Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:

105.0 all locations

Adjustable Trip Setting Current Range Per Pole In Amps:

+1500.0 to 3000.0 ac all locations

Trip Delay Time In Seconds Per Rated Continuous Current:

25.000 at 600 pct all locations

Trip Release Ambient Temperature Rating:

50.0 degrees celsius all locations

Criticality Code Justification:

Feat

Special Features:

For use with new style a fuses only

Frequency In Hertz:

60.0 all locations

Terminal Type And Quantity:

6 screw

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A030a0