NSN 5925-01-222-3650

Circuit Breaker - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5925-01-222-3650

Body Style:
Single pole type
Overall Length:
50.8 millimeters
Body Width:
19.81 millimeters
Case Material:
Metal
Center To Center Distance Between Terminals Parallel To Length:
Between 17.14 millimeters and 17.27 millimeters
Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:
39.62 millimeters
Fragility Factor:
Moderately rugged
End Application:
3950-01-110-9224, crane, mobile
Mounting Surface To Terminal End Distance:
34.97 millimeters
Pole Quantity:
1
Mounting Facility Type And Quantity:
2 terminal
Storage Type:
General purpose warehouse
Maximum Continuous Load Current Rating Per Pole:
20.0 amperes dc single location
Operating Voltage Type And Rating Per Pole In Volts:
12.0 dc single location
Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:
1000.0 dc single location
Circuit Protection Type:
Overcurrent single location
Trip Release Method:
Thermal single location
Trip Release Characteristic:
Instantaneous single location
Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:
125.0 all locations
Reset Method:
Automatic
Internal Trip Release Configuration:

Series trip single location

NSN 5925-01-222-3650

Circuit Breaker - Page 2 of 2



Inclosure Protection Type For Which Designed:
Hermetically sealed
Trip Release Ambient Tempurature Rating:
25.0 degrees celsius single location
Terminal Type And Quantity:
2 threaded stud
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A030a0