

View Online at <https://aerobasegroup.com/nsn/5925-01-222-4379>

Body Style:

Multipole-multiple actuator type

Body Length:

7.120 inches

Body Width:

6.000 inches

Case Material:

Plastic

Center To Center Distance Between Terminals Parallel To Length:

5.940 inches

Center To Center Distance Between Terminals Parallel To Width:

1.500 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

3.828 inches

Switch Contact Arrangement:

Single pole, double throw

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

1.500 inches

Fragility Factor:

Moderately rugged

Boss Height:

0.220 inches

Mounting Surface To Terminal End Distance:

4.300 inches

Pole Quantity:

4

Arc Quenching Method:

Deion

Mounting Facility Type And Quantity:

8 threaded hole

Storage Type:

General purpose warehouse

Thready Qty Per Inch (tpi):

32

Maximum Continuous Load Current Rating Per Pole:

45.0 amperes ac second location

Operating Voltage Type And Rating Per Pole In Volts:

240.0 ac third location

Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:

18000.0 ac third location

Circuit Protection Type:

Overcurrent all locations

Trip Release Method:

Magnetic all locations

Trip Release Characteristic:

Time delay all locations

Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:

150.0 all locations

Reset Method:

Manual

Main Contact Tripping Mechanism Type:

Trip free

Manual Actuator Type And Quantity:

4 toggle

Actuator Function:

Trip-reset

Actuator Position Designation:

At each pole

External Actuator Linkage Arrangement:

One, two, three, and four linked

Auxiliary Switch Function And Quantity:

2 control

Internal Trip Release Configuration:

Series trip third location

Thread Size:

0.190 inches

Switch Location And Position Designation:

Internal at each pole

Trip Delay Time In Seconds Per Rated Continuous Current:

0.900 at 200 pct and 1.300 at 200 pct fourth location

Inclosure Protection Type For Which Designed:

General purpose

Switch Terminal Type:

Tab, solder lug

Switch Current Rating And Type In Amps:

10.0 ac and 10.0 dc

Switch Voltage Rating And Type In Volts:

250.0 ac and 30.0 dc

Special Features:

Relay coil rated at 24.0 vdc, 16.0 ohms

Frequency In Hertz:

400.0 third location

Thread Series Designator:

Unc

Terminal Type And Quantity:

8 threaded stud

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A030a0