

View Online at <https://aerobasegroup.com/nsn/5925-01-222-7441>

Body Style:

Multipole-single actuator type

Bushing Length:

0.281 inches

Body Length:

1.094 inches

Body Width:

2.380 inches

Body Height:

1.600 inches

Case Material:

Plastic

Center To Center Distance Between Terminals Parallel To Length:

Between 0.673 inches and 0.805 inches

Pole Quantity:

3

Mounting Facility Type And Quantity:

1 threaded bushing

Thready Qty Per Inch (tpi):

32

Maximum Continuous Load Current Rating Per Pole:

5.0 amperes ac all locations

Operating Voltage Type And Rating Per Pole In Volts:

120.0 ac all locations

Circuit Protection Type:

Overcurrent all locations

Trip Release Characteristic:

Time delay all locations

Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:

140.0 all locations

Reset Method:

Manual

Main Contact Tripping Mechanism Type:

Trip free

Manual Actuator Type And Quantity:

1 push-pull

Actuator Function:

Trip-reset

Thread Size:

0.469 inches

Trip Delay Time In Seconds Per Rated Continuous Current:

2.500 at 200 pct and 40.000 at 200 pct all locations

Special Features:

Terminal hardware flatwasher; lockwasher and a tri-wing screw

Thread Series Designator:

Uns

Terminal Type And Quantity:

6 screw

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiiig:

A030a0