

View Online at <https://aerobasegroup.com/nsn/5925-01-222-8169>

**Body Style:**

Rectangular dimensional envelope

**Overall Length:**

12.000 inches

**Overall Height:**

6.812 inches

**Overall Width:**

9.000 inches

**Unthreaded Mounting Hole Diameter:**

0.203 inches

**Pole Quantity:**

3

**Mounting Facility Type And Quantity:**

5 unthreaded hole

**Features Provided:**

Adjustable trip release

**Maximum Continuous Load Current Rating Per Pole:**

150.0 amperes ac all locations

**Operating Voltage Type And Rating Per Pole In Volts:**

500.0 ac all locations

**Circuit Protection Type:**

Overcurrent all locations

**Trip Release Method:**

Thermal-magnetic all locations

**Trip Release Characteristic:**

Instantaneous all locations and time delay all locations

**Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:**

125.0 all locations

**Manual Actuator Type And Quantity:**

1 toggle

**Actuator Function:**

Trip-reset

**Actuator Position Designation:**

At pole two

**Adjustable Trip Setting Current Range Per Pole In Amps:**

+650.0/+1300.0 ac all locations

**Trip Delay Time In Seconds Per Rated Continuous Current:**

270.000 at 200 pct all locations

**Trip Release Ambient Temperature Rating:**

50.0 degrees celsius all locations

**Criticality Code Justification:**

Feat

**Special Features:**

Can only be safely used with new type fuse.

**Frequency In Hertz:**

60.0 all locations

**Terminal Type And Quantity:**

6 compression

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiiig:**

A030a0