## NSN 5925-01-223-1066

Circuit Breaker Tripper - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5925-01-223-1066

## Body Style:

Rectangular dimensional envelope

**Overall Length:** 

17.938 inches

## **Overall Height:**

9.000 inches

## **Overall Width:**

11.063 inches

#### **Unthreaded Mounting Hole Diameter:**

0.250 inches

**Fragility Factor:** 

Moderately rugged

## **Pole Quantity:**

3

#### Arc Quenching Method:

Deion

## Mounting Facility Type And Quantity:

5 unthreaded hole

## Storage Type:

General purpose warehouse

## Maximum Continuous Load Current Rating Per Pole:

300.0 amperes ac all locations

## **Operating Voltage Type And Rating Per Pole In Volts:**

500.0 ac all locations

#### **Circuit Protection Type:**

Overcurrent all locations

## **Trip Release Method:**

Thermal-magnetic all locations

## Trip Release Characteristic:

Instantaneous all locations

## Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:

125.0 all locations

## **Trip Release Ambient Tempurature Rating:**

40.0 degrees celsius all locations

## **Criticality Code Justification:**

Feat and supp

## **Special Features:**

For use with suffix a style fuse only

## Frequency In Hertz:

60.0 all locations

#### Supplementary Features:

Motor application

# NSN 5925-01-223-1066

Circuit Breaker Tripper - Page 2 of 2



Terminal Type And Quantity:

6 threaded stud

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A030a0