## NSN 5925-01-223-5749

Circuit Breaker Tripper - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5925-01-223-5749

view Offilitie at https://defobasegroup.com/nsn/0325-01-225-07-49
Body Style:
Rectangular dimensional envelope
Overall Length:
17.938 inches
Overall Height:
6.188 inches
Overall Width:
9.000 inches
Unthreaded Mounting Hole Diameter:
0.250 inches
Pole Quantity:
3
Mounting Facility Type And Quantity:
4 unthreaded hole
Features Provided:
Adjustable trip release
Maximum Continuous Load Current Rating Per Pole:
400.0 amperes ac all locations
Operating Voltage Type And Rating Per Pole In Volts:
500.0 ac all locations
Circuit Protection Type:
Overcurrent all locations
Trip Release Method:
Thermal-magnetic all locations
Trip Release Characteristic:
Instantaneous all locations
Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:
125.0 all locations
Manual Actuator Type And Quantity:
1 toggle
Actuator Function:
Trip-reset
Actuator Position Designation:
At pole two
Adjustable Trip Setting Current Range Per Pole In Amps:
+1380.0 to 2280.0 ac all locations
Trip Release Ambient Tempurature Rating:
50.0 degrees celsius all locations
Criticality Code Justification:
Feat

**Special Features:** 

Can only be safely used with new type fuse

## NSN 5925-01-223-5749

Circuit Breaker Tripper - Page 2 of 2



	Freq	uency	In	Hertz
--	------	-------	----	-------

60.0 all locations

**Terminal Type And Quantity:** 

6 compression

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A030a0