NSN 5925-01-223-6380

Circuit Breaker - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5925-01-223-6380

Body Style:
Multipole-multiple actuator type
Body Length:
7.120 inches
Body Width:
4.500 inches
Case Material:
Plastic
Center To Center Distance Between Terminals Parallel To Length:
5.940 inches
Center To Center Distance Between Terminals Parallel To Width:
1.500 inches
Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:
2.812 inches and 3.828 inches
Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:
1.500 inches
Boss Height:
0.220 inches
Mounting Surface To Terminal End Distance:
4.090 inches
Pole Quantity:
3
Mounting Facility Type And Quantity:
10 threaded hole
Storage Type:
General purpose warehouse
Thready Qty Per Inch (tpi):
32
Maximum Continuous Load Current Rating Per Pole:
100.0 amperes ac all locations
Operating Voltage Type And Rating Per Pole In Volts:
240.0 ac third location
Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:
18000.0 ac all locations
Circuit Protection Type:
Overcurrent all locations
Trip Release Method:
Magnetic-hydraulic all locations
Trip Release Characteristic:
Time delay all locations
Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:
150.0 all locations

NSN 5925-01-223-6380

Circuit Breaker - Page 2 of 2



Reset Method:
Manual
Main Contact Tripping Mechanism Type:
Trip free
Manual Actuator Type And Quantity:
3 toggle
Actuator Function:
Trip-reset
Actuator Position Designation:
At each pole
Internal Trip Release Configuration:
Series trip third location
Thread Size:
0.190 inches
Trip Delay Time In Seconds Per Rated Continuous Current:
2.000 at 200 pct and 15.000 at 200 pct all locations
Inclosure Protection Type For Which Designed:
Fungus resistant
Frequency In Hertz:
50.0 or 60.0 or 400.0 all locations
Thread Series Designator:
Unf
Terminal Type And Quantity:
8 threaded stud
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A030a0