

View Online at <https://aerobasegroup.com/nsn/5925-01-223-9230>

Body Style:

Multipole-single actuator type

Bushing Length:

Between 0.615 inches and 0.635 inches

Body Length:

Between 1.990 inches and 2.010 inches

Body Width:

Between 1.490 inches and 1.510 inches

Case Material:

Plastic

Center To Center Distance Between Terminals Parallel To Length:

Between 1.520 inches and 1.540 inches

Center To Center Distance Between Terminals Parallel To Width:

Between 0.740 inches and 0.760 inches

Fragility Factor:

Moderately rugged

End Application:

5895-01-108-5631

Mounting Surface To Terminal End Distance:

Between 2.222 inches and 2.242 inches

Pole Quantity:

2

Arc Quenching Method:

Magnetic blowout

Mounting Facility Type And Quantity:

1 threaded bushing w/panel seal

Storage Type:

General purpose warehouse

Thready Qty Per Inch (tpi):

32

Maximum Continuous Load Current Rating Per Pole:

7.0 amperes ac first location

Operating Voltage Type And Rating Per Pole In Volts:

250.0 ac all locations

Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:

1000.0 ac all locations

Circuit Protection Type:

Overcurrent all locations

Trip Release Method:

Magnetic all locations

Trip Release Characteristic:

Time delay all locations

Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:

125.0 all locations

Reset Method:

Manual

Main Contact Tripping Mechanism Type:

Trip free

Manual Actuator Type And Quantity:

1 toggle

Actuator Function:

Trip-reset

Actuator Position Designation:

At pole two

Internal Trip Release Configuration:

Series trip all locations

Thread Size:

0.500 inches

Trip Delay Time In Seconds Per Rated Continuous Current:

0.150 at 200 pct and 1.600 at 200 pct first location

Inclosure Protection Type For Which Designed:

Fungus resistant

Frequency In Hertz:

50.0 or 60.0 all locations

Unpackaged Unit Weight:

6.000 ounces

Thread Series Designator:

Un

Terminal Type And Quantity:

4 tab w/screw

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A030a0