

View Online at <https://aerobasegroup.com/nsn/5925-01-223-9335>

Body Style:

Single pole type

Body Length:

1.610 inches

Body Width:

0.695 inches

Body Height:

1.545 inches

Case Material:

Plastic

Fragility Factor:

Moderately rugged

Boss Height:

0.125 inches

Pole Quantity:

1

Arc Quenching Method:

Deion

Mounting Facility Type And Quantity:

2 clip

Storage Type:

General purpose warehouse

Features Provided:

High inrush protection

Maximum Continuous Load Current Rating Per Pole:

10.0 amperes ac single location

Operating Voltage Type And Rating Per Pole In Volts:

120.0 ac single location

Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:

1000.0 ac single location

Circuit Protection Type:

Overcurrent single location

Trip Release Method:

Magnetic single location

Trip Release Characteristic:

Time delay single location

Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:

125.0 single location

Reset Method:

Manual

Main Contact Tripping Mechanism Type:

Trip free

Manual Actuator Type And Quantity:

1 toggle

Actuator Function:

Trip-reset

Actuator Position Designation:

At pole one

Internal Trip Release Configuration:

Series trip single location

Trip Delay Time In Seconds Per Rated Continuous Current:

1.150 at 200 pct and 7.000 at 200 pct single location

Inclsure Protection Type For Which Designed:

General purpose

Special Features:

Rocker type actuator

Frequency In Hertz:

50.0 or 60.0 single location

Unpackaged Unit Weight:

1.300 ounces

Supplementary Features:

Illuminated handle

Terminal Type And Quantity:

2 quick disconnect, male

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A030a0