

View Online at <https://aerobasegroup.com/nsn/5925-01-225-9309>

Body Style:

Multipole-single actuator type

Mounting Slot Width:

0.094 inches

Body Length:

6.000 inches

Body Width:

2.750 inches

Body Height:

3.375 inches

Case Material:

Plastic

Center To Center Distance Between Terminals Parallel To Length:

4.000 inches

Center To Center Distance Between Terminals Parallel To Width:

1.000 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

4.500 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

1.000 inches

Fragility Factor:

Moderately rugged

Boss Height:

0.125 inches

Pole Quantity:

2

Mounting Facility Type And Quantity:

4 slot

Storage Type:

General purpose warehouse

Special Handling Feature:

Magnetic

Maximum Continuous Load Current Rating Per Pole:

100.0 amperes ac all locations

Operating Voltage Type And Rating Per Pole In Volts:

480.0 ac all locations

Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:

14000.0 ac all locations

Circuit Protection Type:

Overcurrent all locations

Trip Release Method:

Thermal-magnetic all locations

Trip Release Characteristic:

Time delay all locations

Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:

135.0 all locations

Reset Method:

Manual

Main Contact Tripping Mechanism Type:

Trip free

Manual Actuator Type And Quantity:

1 toggle

Actuator Function:

Trip-reset

Actuator Position Designation:

At pole one

Trip Delay Time In Seconds Per Rated Continuous Current:

6.000 at 200 pct all locations

Inclosure Protection Type For Which Designed:

Corrosion resistant

Trip Release Ambient Temperature Rating:

40.0 degrees celsius all locations

Frequency In Hertz:

60.0 all locations

Test Data Document:

81348-w-c-375 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Terminal Type And Quantity:

4 compression

Specification Data:

81348-w-c-375/17 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A030a0