

View Online at <https://aerobasegroup.com/nsn/5925-01-226-4960>

Body Style:

Rectangular dimensional envelope

Overall Length:

3.688 inches

Overall Height:

4.250 inches

Overall Width:

3.250 inches

Case Material:

Plastic

Unthreaded Mounting Hole Diameter:

0.172 inches

Pole Quantity:

3

Mounting Facility Type And Quantity:

4 unthreaded hole

Maximum Continuous Load Current Rating Per Pole:

20.0 amperes ac all locations

Operating Voltage Type And Rating Per Pole In Volts:

115.0 ac all locations

Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:

216.0 ac all locations

Circuit Protection Type:

Overcurrent all locations

Trip Release Method:

Thermal all locations

Auxiliary Trip Coil Voltage Type And Rating In Volts:

115.0 ac all locations

Trip Release Characteristic:

Instantaneous all locations

Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:

138.0 all locations

Ultimate Trip Time Per Pole In Seconds:

60.000 all locations

Reset Method:

Electric

Main Contact Tripping Mechanism Type:

Trip free

Internal Trip Release Configuration:

Series trip w/auxiliary load terminal and remote trip feature all locations

Trip Release Duty Cycle:

Continuous all locations

Reset Actuator Voltage Rating And Type In Volts:

115.0 ac

Trip Release Ambient Temperature Rating:

-54.0 degrees celsius and 71.0 degrees celsius all locations

Frequency In Hertz:

400.0 all locations

Terminal Type And Quantity:

6 threaded stud

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A030a0