

View Online at <https://aerobasegroup.com/nsn/5925-01-226-4960>

**Body Style:**

Rectangular dimensional envelope

**Overall Length:**

3.688 inches

**Overall Height:**

4.250 inches

**Overall Width:**

3.250 inches

**Case Material:**

Plastic

**Unthreaded Mounting Hole Diameter:**

0.172 inches

**Pole Quantity:**

3

**Mounting Facility Type And Quantity:**

4 unthreaded hole

**Maximum Continuous Load Current Rating Per Pole:**

20.0 amperes ac all locations

**Operating Voltage Type And Rating Per Pole In Volts:**

115.0 ac all locations

**Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:**

216.0 ac all locations

**Circuit Protection Type:**

Overcurrent all locations

**Trip Release Method:**

Thermal all locations

**Auxiliary Trip Coil Voltage Type And Rating In Volts:**

115.0 ac all locations

**Trip Release Characteristic:**

Instantaneous all locations

**Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:**

138.0 all locations

**Ultimate Trip Time Per Pole In Seconds:**

60.000 all locations

**Reset Method:**

Electric

**Main Contact Tripping Mechanism Type:**

Trip free

**Internal Trip Release Configuration:**

Series trip w/auxiliary load terminal and remote trip feature all locations

**Trip Release Duty Cycle:**

Continuous all locations

**Reset Actuator Voltage Rating And Type In Volts:**

115.0 ac

**Trip Release Ambient Temperature Rating:**

-54.0 degrees celsius and 71.0 degrees celsius all locations

**Frequency In Hertz:**

400.0 all locations

**Terminal Type And Quantity:**

6 threaded stud

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A030a0