

View Online at <https://aerobasegroup.com/nsn/5925-01-227-4045>

Body Style:

Rectangular dimensional envelope

Overall Length:

2.000 inches

Overall Height:

2.415 inches

Overall Width:

1.320 inches

Case Material:

Plastic

Pole Quantity:

2

Mounting Facility Type And Quantity:

4 clip

Maximum Continuous Load Current Rating Per Pole:

7.5 amperes ac first location

Operating Voltage Type And Rating Per Pole In Volts:

250.0 ac first location

Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:

200.0 ac first location

Circuit Protection Type:

Overcurrent all locations

Trip Release Method:

Magnetic all locations

Trip Release Characteristic:

Time delay first location

Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:

125.0 first location

Ultimate Trip Time Per Pole In Seconds:

60.000 first location

Reset Method:

Manual

Manual Actuator Type And Quantity:

2 push button

Actuator Function:

Trip-reset

Internal Trip Release Configuration:

Relay trip second location

Trip Release Duty Cycle:

Continuous all locations

Inclosure Protection Type For Which Designed:

Shock resistant and vibration resistant

Trip Release Ambient Temperature Rating:

-40.0 degrees celsius and 85.0 degrees celsius all locations

Special Features:

Lighted actuator red incondescant 3-5 volt

Frequency In Hertz:

50.0 or 60.0 first location

Terminal Type And Quantity:

7 quick disconnect, male

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A030a0