

View Online at <https://aerobasegroup.com/nsn/5925-01-227-4045>

**Body Style:**

Rectangular dimensional envelope

**Overall Length:**

2.000 inches

**Overall Height:**

2.415 inches

**Overall Width:**

1.320 inches

**Case Material:**

Plastic

**Pole Quantity:**

2

**Mounting Facility Type And Quantity:**

4 clip

**Maximum Continuous Load Current Rating Per Pole:**

7.5 amperes ac first location

**Operating Voltage Type And Rating Per Pole In Volts:**

250.0 ac first location

**Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:**

200.0 ac first location

**Circuit Protection Type:**

Overcurrent all locations

**Trip Release Method:**

Magnetic all locations

**Trip Release Characteristic:**

Time delay first location

**Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:**

125.0 first location

**Ultimate Trip Time Per Pole In Seconds:**

60.000 first location

**Reset Method:**

Manual

**Manual Actuator Type And Quantity:**

2 push button

**Actuator Function:**

Trip-reset

**Internal Trip Release Configuration:**

Relay trip second location

**Trip Release Duty Cycle:**

Continuous all locations

**Inclosure Protection Type For Which Designed:**

Shock resistant and vibration resistant

**Trip Release Ambient Temperature Rating:**

-40.0 degrees celsius and 85.0 degrees celsius all locations

**Special Features:**

Lighted actuator red incondescant 3-5 volt

**Frequency In Hertz:**

50.0 or 60.0 first location

**Terminal Type And Quantity:**

7 quick disconnect, male

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A030a0