

View Online at <https://aerobasegroup.com/nsn/5925-01-227-4048>

**Body Style:**

Rectangular dimensional envelope

**Overall Length:**

3.250 inches

**Overall Height:**

4.250 inches

**Overall Width:**

1.250 inches

**Case Material:**

Plastic

**Unthreaded Mounting Hole Diameter:**

Between 0.167 inches and 0.177 inches

**Pole Quantity:**

1

**Mounting Facility Type And Quantity:**

2 unthreaded hole

**Maximum Continuous Load Current Rating Per Pole:**

20.0 amperes ac single location

**Operating Voltage Type And Rating Per Pole In Volts:**

115.0 ac single location

**Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:**

3600.0 ac single location

**Circuit Protection Type:**

Overcurrent single location

**Trip Release Method:**

Thermal single location

**Auxiliary Trip Coil Voltage Type And Rating In Volts:**

115.0 ac single location

**Trip Release Characteristic:**

Instantaneous single location

**Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:**

138.0 single location

**Ultimate Trip Time Per Pole In Seconds:**

60.000 single location

**Reset Method:**

Electric

**Main Contact Tripping Mechanism Type:**

Trip free

**Internal Trip Release Configuration:**

Series trip w/auxiliary load terminal and remote trip feature single location

**Trip Release Duty Cycle:**

Continuous single location

**Reset Actuator Voltage Rating And Type In Volts:**

115.0 ac

**Trip Release Ambient Temperature Rating:**

-54.0 degrees celsius and 71.0 degrees celsius single location

**Frequency In Hertz:**

400.0 single location

**Terminal Type And Quantity:**

2 threaded stud

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A030a0