

View Online at <https://aerobasegroup.com/nsn/5925-01-227-4048>

Body Style:

Rectangular dimensional envelope

Overall Length:

3.250 inches

Overall Height:

4.250 inches

Overall Width:

1.250 inches

Case Material:

Plastic

Unthreaded Mounting Hole Diameter:

Between 0.167 inches and 0.177 inches

Pole Quantity:

1

Mounting Facility Type And Quantity:

2 unthreaded hole

Maximum Continuous Load Current Rating Per Pole:

20.0 amperes ac single location

Operating Voltage Type And Rating Per Pole In Volts:

115.0 ac single location

Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:

3600.0 ac single location

Circuit Protection Type:

Overcurrent single location

Trip Release Method:

Thermal single location

Auxiliary Trip Coil Voltage Type And Rating In Volts:

115.0 ac single location

Trip Release Characteristic:

Instantaneous single location

Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:

138.0 single location

Ultimate Trip Time Per Pole In Seconds:

60.000 single location

Reset Method:

Electric

Main Contact Tripping Mechanism Type:

Trip free

Internal Trip Release Configuration:

Series trip w/auxiliary load terminal and remote trip feature single location

Trip Release Duty Cycle:

Continuous single location

Reset Actuator Voltage Rating And Type In Volts:

115.0 ac

Trip Release Ambient Temperature Rating:

-54.0 degrees celsius and 71.0 degrees celsius single location

Frequency In Hertz:

400.0 single location

Terminal Type And Quantity:

2 threaded stud

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A030a0