NSN 5925-01-229-7162

Circuit Breaker - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5925-01-229-7162

Thread Pitch Diameters:
+0.1177 to 0.1214 inches
Body Style:
Multipole-multiple actuator type
Body Length:
2.500 inches
Body Width:
1.500 inches
Case Material:
Plastic
Center To Center Distance Between Terminals Parallel To Length:
1.938 inches
Center To Center Distance Between Terminals Parallel To Width:
0.750 inches
Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:
2.062 inches
Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:
0.750 inches
Fragility Factor:
Moderately rugged
Boss Height:
0.140 inches
Mounting Surface To Terminal End Distance:
2.471 inches
Pole Quantity:
2
Arc Quenching Method:
Magnetic blowout
Mounting Facility Type And Quantity:
4 threaded hole
Storage Type:
General purpose warehouse
Special Handling Feature:
Magnetic
Thready Qty Per Inch (tpi):
32
Maximum Continuous Load Current Rating Per Pole:
8.0 amperes ac all locations
Operating Voltage Type And Rating Per Pole In Volts:
240.0 ac second location
Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:

1000.0 ac all locations

NSN 5925-01-229-7162

Circuit Breaker - Page 2 of 2



Circuit Protection Type:
Undervoltage first location
Trip Release Method:
Magnetic all locations
Trip Release Characteristic:
Instantaneous all locations
Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:
115.0 all locations
Reset Method:
Manual
Main Contact Tripping Mechanism Type:
Trip free
Manual Actuator Type And Quantity:
2 toggle
Actuator Function:
Trip-reset
Actuator Position Designation:
At each pole
External Actuator Linkage Arrangement:
One and two linked
Internal Trip Release Configuration:
Shunt trip first location
Thread Size:
0.138 inches
Inclosure Protection Type For Which Designed:
Fungus resistant and moisture resistant
Frequency In Hertz:
60.0 all locations
Unpackaged Unit Weight:
6.500 ounces
Thread Series Designator:
Unc
Terminal Type And Quantity:
5 threaded stud
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A030a0