NSN 5925-01-229-8656



Circuit Breaker - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5925-01-229-8656 **Body Style:** Multipole-single actuator type **Mounting Slot Width:** 0.164 inches **Body Length:** 6.000 inches **Body Width:** 4.230 inches **Body Height: 3.120 inches Case Material: Plastic Center To Center Distance Between Terminals Parallel To Length:** 4.880 inches **Center To Center Distance Between Terminals Parallel To Width:** 1.380 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Length: 4.500 inches **Switch Contact Arrangement:** Single pole, double throw Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: 1.380 inches **Boss Height:** 0.260 inches **Pole Quantity:** 3 **Arc Quenching Method: Mounting Facility Type And Quantity:** 4 slot Storage Type: General purpose warehouse **Maximum Continuous Load Current Rating Per Pole:** 100.0 amperes ac all locations **Operating Voltage Type And Rating Per Pole In Volts:** 480.0 ac all locations Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:

14000.0 ac all locations

Circuit Protection Type:

Overcurrent all locations

Trip Release Method:

Magnetic-hydraulic all locations

NSN 5925-01-229-8656

Circuit Breaker - Page 2 of 2



Trip Release Characteristic:
Time delay all locations
Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:
125.0 all locations
Reset Method:
Manual
Main Contact Tripping Mechanism Type:
Trip free
Manual Actuator Type And Quantity:
1 toggle
Actuator Function:
Trip-reset
Actuator Position Designation:
At pole two
Auxiliary Switch Function And Quantity:
1 alarm
Internal Trip Release Configuration:
Series trip all locations
Switch Location And Position Designation:
Internal at pole one
Trip Delay Time In Seconds Per Rated Continuous Current:
1.500 at 200 pct and 135.000 at 200 pct all locations
Inclosure Protection Type For Which Designed:
Moisture resistant and shock resistant and vibration resistant
Switch Current Rating And Type In Amps:
5.0 ac
Switch Voltage Rating And Type In Volts:
125.0 ac
Frequency In Hertz:
50.0 or 60.0 all locations
Unpackaged Unit Weight:
3.300 pounds
Terminal Type And Quantity:
6 compression
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A030a0