

View Online at <https://aerobasegroup.com/nsn/5925-01-230-4059>

Body Style:

Single pole type

Bushing Length:

0.500 inches

Body Length:

1.260 inches

Body Width:

0.550 inches

Case Material:

Plastic

Center To Center Distance Between Terminals Parallel To Length:

0.690 inches

Fragility Factor:

Moderately rugged

Mounting Surface To Terminal End Distance:

1.530 inches

Pole Quantity:

1

Mounting Facility Type And Quantity:

1 threaded bushing

Storage Type:

General purpose warehouse

Thready Qty Per Inch (tpi):

27

Maximum Continuous Load Current Rating Per Pole:

10.0 amperes ac and 10.0 amperes dc single location

Operating Voltage Type And Rating Per Pole In Volts:

250.0 ac and 28.0 dc single location

Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:

1000.0 ac and 1000.0 dc single location

Circuit Protection Type:

Overcurrent single location

Trip Release Method:

Thermal single location

Trip Release Characteristic:

Time delay single location

Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:

125.0 single location

Reset Method:

Manual

Main Contact Tripping Mechanism Type:

Trip free

Manual Actuator Type And Quantity:

1 push button

Actuator Function:

Reset

Actuator Position Designation:

At pole one

Internal Trip Release Configuration:

Series trip single location

Thread Size:

0.375 inches

Trip Delay Time In Seconds Per Rated Continuous Current:

5.000 at 200 pct and 25.000 at 200 pct single location

Inclosure Protection Type For Which Designed:

General purpose

Trip Release Ambient Temperature Rating:

21.0 degrees celsius single location

Frequency In Hertz:

60.0 single location

Unpackaged Unit Weight:

19.0 grams

Thread Series Designator:

Uns

Terminal Type And Quantity:

2 quick disconnect, male

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiiig:

A030a0