

View Online at <https://aerobasegroup.com/nsn/5925-01-230-4481>

Body Style:

Single pole type

Overall Length:

2.000 inches

Body Width:

0.500 inches

Case Material:

Metal

Center To Center Distance Between Terminals Parallel To Length:

0.678 inches

Unthreaded Mounting Hole Diameter:

0.281 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

1.560 inches

Fragility Factor:

Moderately rugged

Mounting Surface To Terminal End Distance:

1.332 inches

Pole Quantity:

1

Arc Quenching Method:

Deion

Mounting Facility Type And Quantity:

2 unthreaded hole

Storage Type:

General purpose warehouse

Maximum Continuous Load Current Rating Per Pole:

30.0 amperes dc single location

Operating Voltage Type And Rating Per Pole In Volts:

12.0 dc single location

Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:

500.0 dc single location

Circuit Protection Type:

Overcurrent single location

Trip Release Method:

Thermal single location

Trip Release Characteristic:

Time delay single location

Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:

125.0 single location

Reset Method:

Automatic

Internal Trip Release Configuration:

Series trip single location

Trip Delay Time In Seconds Per Rated Continuous Current:

60.000 at 200 pct single location

Inclsoure Protection Type For Which Designed:

General purpose

Trip Release Ambient Temperature Rating:

240.0 degrees fahrenheit single location

Terminal Type And Quantity:

2 threaded stud

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A030a0