## NSN 5925-01-231-4235

Circuit Breaker - Page 1 of 2

Time delay all locations



View Online at https://aerobasegroup.com/nsn/5925-01-231-4235

Body Style:
Multipole-multiple actuator type
Body Length:
2.000 inches
Body Width:
2.265 inches
Case Material:
Plastic
Center To Center Distance Between Terminals Parallel To Length:
1.530 inches
Center To Center Distance Between Terminals Parallel To Width:
0.750 inches
Distance Between Centerlines Of Mounting Facilities Parallel To Body Length
1.660 inches
Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:
0.750 inches
End Application:
Communications terminal, satellite an/tsc-94 (v)
Boss Height:
0.130 inches
Mounting Surface To Terminal End Distance:
2.032 inches
Pole Quantity:
3
Mounting Facility Type And Quantity:
6 threaded hole
Storage Type:
General purpose warehouse
Thready Qty Per Inch (tpi):
32
Maximum Continuous Load Current Rating Per Pole:
15.0 amperes ac all locations
Operating Voltage Type And Rating Per Pole In Volts:
250.0 ac all locations
Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:
1000.0 ac all locations
Circuit Protection Type:
Overvoltage first location
Trip Release Method:
Magnetic all locations
Trip Release Characteristic:

## **NSN 5925-01-231-4235** Circuit Breaker - Page 2 of 2



Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:
125.0 all locations
Reset Method:
Manual
Main Contact Tripping Mechanism Type:
Trip free
Manual Actuator Type And Quantity:
3 toggle
Actuator Function:
Trip-reset
Actuator Position Designation:
At each pole
External Actuator Linkage Arrangement:
One, two, and three linked
Internal Trip Release Configuration:
Series trip second location
Thread Size:
0.138 inches
Trip Delay Time In Seconds Per Rated Continuous Current:
0.100 at 200 pct and 0.550 at 200 pct all locations
Inclosure Protection Type For Which Designed:
Fungus resistant and moisture resistant
Frequency In Hertz:
50.0 or 60.0 all locations
Unpackaged Unit Weight:
6.600 ounces
Thread Series Designator:
Unc
Terminal Type And Quantity:
10 tab w/screw
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A030a0