

View Online at <https://aerobasegroup.com/nsn/5925-01-233-4735>

Body Style:

Single pole type

Body Length:

Between 2.255 inches and 2.305 inches

Body Width:

2.250 inches

Case Material:

Plastic

Center To Center Distance Between Terminals Parallel To Length:

Between 1.925 inches and 1.955 inches

Unthreaded Mounting Hole Diameter:

Between 0.151 inches and 0.161 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

Between 2.050 inches and 2.070 inches

Boss Height:

Between 0.135 inches and 0.165 inches

Mounting Surface To Terminal End Distance:

2.506 inches

Pole Quantity:

3

Mounting Facility Type And Quantity:

6 unthreaded hole

Maximum Continuous Load Current Rating Per Pole:

5.0 amperes ac all locations

Operating Voltage Type And Rating Per Pole In Volts:

250.0 ac and 65.0 dc all locations

Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:

2100.0 ac all locations

Circuit Protection Type:

Overcurrent all locations

Trip Release Method:

Magnetic all locations

Trip Release Characteristic:

Time delay all locations

Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:

115.0 all locations

Reset Method:

Manual

Main Contact Tripping Mechanism Type:

Trip free

Manual Actuator Type And Quantity:

3 toggle

Internal Trip Release Configuration:

Series trip all locations

Trip Delay Time In Seconds Per Rated Continuous Current:

5.000 at 150 pct and 70.000 at 150 pct all locations

Frequency In Hertz:

400.0 all locations

Terminal Type And Quantity:

6 threaded stud

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A030a0