NSN 5925-01-233-4736

Circuit Breaker - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5925-01-233-4736

Body Style: Single pole type **Body Length:** Between 2.480 inches and 2.500 inches **Body Width:** 0.750 inches **Case Material:** Plastic **Center To Center Distance Between Terminals Parallel To Length:** Between 1.925 inches and 1.955 inches **Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:** Between 2.050 inches and 2.070 inches **Fragility Factor:** Moderately rugged **Boss Height:** Between 0.135 inches and 0.165 inches **Mounting Surface To Terminal End Distance:** 2.491 inches **Pole Quantity: Arc Quenching Method:** Magnetic blowout **Mounting Facility Type And Quantity:** 2 threaded hole Storage Type: General purpose warehouse **Special Handling Feature:** Magnetic **Maximum Continuous Load Current Rating Per Pole:** 30.0 amperes dc single location Operating Voltage Type And Rating Per Pole In Volts: 65.0 dc single location Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps: 2000.0 dc single location **Circuit Protection Type:** Overcurrent single location **Trip Release Method:** Magnetic single location **Trip Release Characteristic:** Time delay single location **Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:**

125.0 single location

NSN 5925-01-233-4736 Circuit Breaker - Page 2 of 2



Reset Method:
Manual
Main Contact Tripping Mechanism Type:
Trip free
Manual Actuator Type And Quantity:
1 toggle
Actuator Function:
Trip-reset
Actuator Position Designation:
At pole one
Internal Trip Release Configuration:
Series trip single location
Thread Size:
3.0 millimeters
Thread Pitch In Millimeters:
0.50
Trip Delay Time In Seconds Per Rated Continuous Current:
0.700 at 200 pct and 10.000 at 200 pct single location
Inclosure Protection Type For Which Designed:
Fungus resistant and moisture resistant and salt spray proof and shock resistant and vibration resistant
Unpackaged Unit Weight:
3.700 ounces
Thread Series Designator:
lso s
Terminal Type And Quantity:
2 threaded stud
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A030a0