## NSN 5925-01-233-4737

Circuit Breaker - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5925-01-233-4737

**Body Style:** Single pole type **Body Length:** Between 2.480 inches and 2.500 inches **Body Width:** 0.750 inches **Case Material:** Plastic **Center To Center Distance Between Terminals Parallel To Length:** Between 1.925 inches and 1.955 inches **Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:** Between 2.050 inches and 2.070 inches **Fragility Factor:** Moderately rugged **Boss Height:** Between 0.135 inches and 0.165 inches **Mounting Surface To Terminal End Distance:** 2.491 inches **Pole Quantity: Arc Quenching Method:** Magnetic blowout **Mounting Facility Type And Quantity:** 2 threaded hole Storage Type: General purpose warehouse **Special Handling Feature:** Magnetic **Maximum Continuous Load Current Rating Per Pole:** 5.0 amperes dc single location Operating Voltage Type And Rating Per Pole In Volts: 65.0 dc single location Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps: 2000.0 dc single location **Circuit Protection Type:** Overcurrent single location **Trip Release Method:** Magnetic single location **Trip Release Characteristic:** Time delay single location **Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:** 

125.0 single location

## NSN 5925-01-233-4737

Circuit Breaker - Page 2 of 2



| Reset Method:  |
|--|
| Manual   |
| Main Contact Tripping Mechanism Type:  |
| Trip free  |
| Manual Actuator Type And Quantity:   |
| 1 toggle   |
| Actuator Function:   |
| Trip-reset   |
| Actuator Position Designation:   |
| At pole one  |
| Internal Trip Release Configuration:   |
| Series trip single location  |
| Thread Size:   |
| 3.0 millimeters  |
| Thread Pitch In Millimeters:   |
| 0.50   |
| Trip Delay Time In Seconds Per Rated Continuous Current:   |
| 16.500 at 200 pct and 70.000 at 200 pct single location  |
| Inclosure Protection Type For Which Designed:  |
| Fungus resistant and moisture resistant and salt spray proof and shock resistant and vibration resistant |
| Unpackaged Unit Weight:  |
| 3.700 ounces   |
| Thread Series Designator:  |
| lso s  |
| Terminal Type And Quantity:  |
| 2 threaded stud  |
| Shelf Life:  |
| N/a  |
| Unit Of Measure:   |
| <del>-</del>   |
| Demilitarization:  |
| No   |
| Fiig:  |
| A030a0   |
|  |
|  |