

View Online at <https://aerobasegroup.com/nsn/5925-01-236-1016>

Body Style:

Multipole-single actuator type

Body Length:

11.000 inches

Body Width:

9.000 inches

Case Material:

Plastic

Center To Center Distance Between Terminals Parallel To Length:

9.875 inches

Center To Center Distance Between Terminals Parallel To Width:

3.000 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

9.875 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

3.000 inches

Fragility Factor:

Moderately rugged

Boss Height:

0.063 inches

Mounting Surface To Terminal End Distance:

9.218 inches

Pole Quantity:

3

Arc Quenching Method:

Magnetic blowout

Mounting Facility Type And Quantity:

4 threaded hole

Storage Type:

General purpose warehouse

Thready Qty Per Inch (tpi):

20

Maximum Continuous Load Current Rating Per Pole:

250.0 amperes ac all locations

Operating Voltage Type And Rating Per Pole In Volts:

500.0 ac all locations and 250.0 dc all locations

Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:

20000.0 ac all locations and 15000.0 dc all locations

Circuit Protection Type:

Overcurrent all locations

Trip Release Method:

Thermal-magnetic all locations

Trip Release Characteristic:

Instantaneous all locations

Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:

125.0 all locations

Reset Method:

Manual

Main Contact Tripping Mechanism Type:

Trip free

Manual Actuator Type And Quantity:

1 toggle

Actuator Function:

Trip-reset

Actuator Position Designation:

At pole two

Thread Size:

0.250 inches

Inclosure Protection Type For Which Designed:

General purpose

Trip Release Ambient Temperature Rating:

50.0 degrees celsius all locations

Special Features:

Mounting hardware included

Frequency In Hertz:

60.0 all locations

Precious Material And Location:

Contact surfaces silver

Precious Material:

Silver

Test Data Document:

81349-mil-c-17361 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Thread Series Designator:

Unc

Terminal Type And Quantity:

6 threaded stud

Specification Data:

81349-mil-c-17361 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

1-000-0