

View Online at <https://aerobasegroup.com/nsn/5925-01-237-7298>

**Body Style:**

Single pole type

**Overall Length:**

1.700 inches

**Overall Width:**

0.530 inches

**Case Material:**

Plastic

**Center To Center Distance Between Terminals Parallel To Length:**

0.450 inches

**Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:**

1.670 inches

**Fragility Factor:**

Moderately rugged

**Boss Height:**

0.125 inches

**Mounting Surface To Terminal End Distance:**

0.840 inches

**Pole Quantity:**

1

**Arc Quenching Method:**

Air

**Mounting Facility Type And Quantity:**

2 clip

**Storage Type:**

General purpose warehouse

**Cubic Measure:**

0.757 cubic inches

**Maximum Continuous Load Current Rating Per Pole:**

3.0 amperes ac single location

**Operating Voltage Type And Rating Per Pole In Volts:**

125.0 ac single location

**Circuit Protection Type:**

Overcurrent single location

**Trip Release Method:**

Magnetic single location

**Trip Release Characteristic:**

Time delay single location

**Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:**

175.0 single location

**Reset Method:**

Manual

**Main Contact Tripping Mechanism Type:**

Trip free

**Manual Actuator Type And Quantity:**

1 push button

**Actuator Function:**

Trip-reset

**Actuator Position Designation:**

At pole one

**Internal Trip Release Configuration:**

Series trip single location

**Trip Delay Time In Seconds Per Rated Continuous Current:**

5.250 at 200 pct single location and 50.000 at 200 pct single location

**Frequency In Hertz:**

60.0 single location

**Terminal Type And Quantity:**

2 tab, solder lug

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A030a0