

View Online at <https://aerobasegroup.com/nsn/5925-01-237-7298>

Body Style:

Single pole type

Overall Length:

1.700 inches

Overall Width:

0.530 inches

Case Material:

Plastic

Center To Center Distance Between Terminals Parallel To Length:

0.450 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

1.670 inches

Fragility Factor:

Moderately rugged

Boss Height:

0.125 inches

Mounting Surface To Terminal End Distance:

0.840 inches

Pole Quantity:

1

Arc Quenching Method:

Air

Mounting Facility Type And Quantity:

2 clip

Storage Type:

General purpose warehouse

Cubic Measure:

0.757 cubic inches

Maximum Continuous Load Current Rating Per Pole:

3.0 amperes ac single location

Operating Voltage Type And Rating Per Pole In Volts:

125.0 ac single location

Circuit Protection Type:

Overcurrent single location

Trip Release Method:

Magnetic single location

Trip Release Characteristic:

Time delay single location

Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:

175.0 single location

Reset Method:

Manual

Main Contact Tripping Mechanism Type:

Trip free

Manual Actuator Type And Quantity:

1 push button

Actuator Function:

Trip-reset

Actuator Position Designation:

At pole one

Internal Trip Release Configuration:

Series trip single location

Trip Delay Time In Seconds Per Rated Continuous Current:

5.250 at 200 pct single location and 50.000 at 200 pct single location

Frequency In Hertz:

60.0 single location

Terminal Type And Quantity:

2 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A030a0