# NSN 5925-01-237-7298

Circuit Breaker - Page 1 of 2

Manual



View Online at https://aerobasegroup.com/nsn/5925-01-237-7298

Body Style:
Single pole type
Overall Length:
1.700 inches
Overall Width:
0.530 inches
Case Material:
Plastic
Center To Center Distance Between Terminals Parallel To Length:
0.450 inches
Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:
1.670 inches
Fragility Factor:
Moderately rugged
Boss Height:
0.125 inches
Mounting Surface To Terminal End Distance:
0.840 inches
Pole Quantity:
1
Arc Quenching Method:
Air
Mounting Facility Type And Quantity:
2 clip
Storage Type:
General purpose warehouse
Cubic Measure:
0.757 cubic inches
Maximum Continuous Load Current Rating Per Pole:
3.0 amperes ac single location
Operating Voltage Type And Rating Per Pole In Volts:
125.0 ac single location
Circuit Protection Type:
Overcurrent single location
Trip Release Method:
Magnetic single location
Trip Release Characteristic:
Trip Release Characteristic: Time delay single location
-
Time delay single location

# NSN 5925-01-237-7298

Circuit Breaker - Page 2 of 2



# Main Contact Tripping Mechanism Type:

Trip free

## Manual Actuator Type And Quantity:

1 push button

Actuator Function:

Trip-reset

## Actuator Position Designation:

At pole one

## Internal Trip Release Configuration:

Series trip single location

## Trip Delay Time In Seconds Per Rated Continuous Current:

5.250 at 200 pct single location and 50.000 at 200 pct single location

### Frequency In Hertz:

60.0 single location

### **Terminal Type And Quantity:**

2 tab, solder lug

Shelf Life:

N/a

---

### Unit Of Measure:

Demilitarization:

No

Fiig:

A030a0