## NSN 5925-01-237-7299

Circuit Breaker - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5925-01-237-7299

**Body Style:** 

Single pole type

**Body Length:** 

Between 1.985 inches and 2.015 inches

**Body Width:** 

Between 0.745 inches and 0.755 inches

Case Material:

Plastic

**Center To Center Distance Between Terminals Parallel To Length:** 

Between 1.555 inches and 1.565 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

Between 1.655 inches and 1.665 inches

**Fragility Factor:** 

Moderately rugged

**Boss Height:** 

Between 0.125 inches and 0.135 inches

**Mounting Surface To Terminal End Distance:** 

Between 1.875 inches and 1.885 inches

**Pole Quantity:** 

4

**Arc Quenching Method:** 

Magnetic blowout

**Mounting Facility Type And Quantity:** 

2 threaded hole

Storage Type:

General purpose warehouse

**Features Provided:** 

High inrush protection

Thready Qty Per Inch (tpi):

32

**Maximum Continuous Load Current Rating Per Pole:** 

10.0 amperes ac single location

**Operating Voltage Type And Rating Per Pole In Volts:** 

250.0 ac single location

Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:

1000.0 ac single location

**Circuit Protection Type:** 

Overcurrent single location

**Trip Release Method:** 

Magnetic-hydraulic single location

**Trip Release Characteristic:** 

Time delay single location

## NSN 5925-01-237-7299

Circuit Breaker - Page 2 of 2



Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:
125.0 single location
Reset Method:
Manual
Main Contact Tripping Mechanism Type:
Trip free
Manual Actuator Type And Quantity:
1 toggle
Actuator Function:
Trip-reset
Actuator Position Designation:
At pole one
Internal Trip Release Configuration:
Series trip single location
Thread Size:
0.138 inches
Trip Delay Time In Seconds Per Rated Continuous Current:
2.500 at 200 pct single location and 25.000 at 200 pct single location
Inclosure Protection Type For Which Designed:
Fungus resistant
Frequency In Hertz:
60.0 single location
Unpackaged Unit Weight:
2.500 ounces
Thread Series Designator:
Unc
Terminal Type And Quantity:
2 quick disconnect, male
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A030a0