

View Online at <https://aerobasegroup.com/nsn/5925-01-237-7937>

**Body Style:**

Multipole-single actuator type

**Bushing Length:**

0.250 inches

**Body Length:**

2.063 inches

**Body Width:**

1.300 inches

**Case Material:**

Plastic

**Center To Center Distance Between Terminals Parallel To Length:**

1.375 inches

**Center To Center Distance Between Terminals Parallel To Width:**

0.750 inches

**Nonturn Device Location:**

At 12 oclock

**Nonturn Device Radius:**

0.375 inches

**Nonturn Device Length:**

0.045 inches

**Nonturn Device Diameter:**

0.093 inches

**Fragility Factor:**

Moderately rugged

**Mounting Surface To Terminal End Distance:**

1.875 inches

**Pole Quantity:**

3

**Arc Quenching Method:**

Magnetic blowout

**Mounting Facility Type And Quantity:**

2 threaded bushing

**Storage Type:**

General purpose warehouse

**Thready Qty Per Inch (tpi):**

32

**Maximum Continuous Load Current Rating Per Pole:**

3.0 amperes ac all locations

**Operating Voltage Type And Rating Per Pole In Volts:**

120.0 ac all locations

**Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:**

300.0 ac all locations

**Circuit Protection Type:**

Overcurrent all locations

**Trip Release Method:**

Thermal-magnetic all locations

**Trip Release Characteristic:**

Instantaneous all locations

**Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:**

138.0 all locations

**Reset Method:**

Manual

**Main Contact Tripping Mechanism Type:**

Trip free

**Manual Actuator Type And Quantity:**

1 push button

**Actuator Function:**

Trip-reset

**Actuator Position Designation:**

At pole two

**Thread Size:**

0.138 inches

**Inclosure Protection Type For Which Designed:**

General purpose

**Trip Release Ambient Temperature Rating:**

-65.0 degrees celsius all locations and 71.0 degrees celsius all locations

**Frequency In Hertz:**

400.0 all locations

**Unpackaged Unit Weight:**

154.0 grams

**Precious Material And Location:**

Plated contacts silver

**Precious Material:**

Silver

**Thread Series Designator:**

Unc

**Terminal Type And Quantity:**

6 threaded stud

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A030a0