## NSN 5925-01-237-8109



Circuit Breaker - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5925-01-237-8109 **Body Style:** Rectangular dimensional envelope **Overall Length:** 2.875 inches **Overall Height:** 1.000 inches **Overall Width:** 2.375 inches **Case Material: Plastic Fragility Factor:** Moderately rugged **Pole Quantity: Mounting Facility Type And Quantity:** 2 terminal Storage Type: General purpose warehouse **Special Handling Feature:** Magnetic **Maximum Continuous Load Current Rating Per Pole:** 20.0 amperes ac single location **Operating Voltage Type And Rating Per Pole In Volts:** 120.0 ac single location Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps: 10000.0 ac single location **Circuit Protection Type:** Overcurrent all locations **Trip Release Method:** Thermal-magnetic all locations **Trip Release Characteristic:** Instantaneous all locations **Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:** 125.0 all locations **Reset Method:** Manual **Main Contact Tripping Mechanism Type:** Trip free **Manual Actuator Type And Quantity:** 1 toggle

Trip-reset

**Actuator Function:** 

## NSN 5925-01-237-8109

Circuit Breaker - Page 2 of 2



Actuator Position Designation:
At pole one
Inclosure Protection Type For Which Designed:
Fungus proof
Trip Release Ambient Tempurature Rating:
25.0 degrees celsius all locations
Frequency In Hertz:
60.0 single location
Unpackaged Unit Weight:
0.400 pounds
Terminal Type And Quantity:
2 bus bar
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A030a0