NSN 5925-01-238-5711

Circuit Breaker - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5925-01-238-5711 **Body Style:** Multipole-single actuator type **Body Length:** 15.500 inches **Body Width:** 8.250 inches **Body Height:** 7.090 inches **Case Material: Plastic Center To Center Distance Between Terminals Parallel To Length:** 9.120 inches **Center To Center Distance Between Terminals Parallel To Width:** 2.750 inches **Unthreaded Mounting Hole Diameter:** 0.250 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Length: 14.250 inches **Switch Contact Arrangement:** Single pole, double throw Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: 2.750 inches **Boss Height:** 0.250 inches **Pole Quantity:** 2 **Mounting Facility Type And Quantity:** 4 unthreaded hole **Features Provided:** Adjustable trip release **Maximum Continuous Load Current Rating Per Pole:** 1200.0 amperes ac all locations **Operating Voltage Type And Rating Per Pole In Volts:** 600.0 ac all locations Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps: 22000.0 ac all locations **Circuit Protection Type:** Undervoltage all locations **Trip Release Method:**

Trip Release Characteristic: Instantaneous all locations

Thermal-magnetic all locations

NSN 5925-01-238-5711

Circuit Breaker - Page 2 of 2



Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:
125.0 all locations
Reset Method:
Manual
Main Contact Tripping Mechanism Type:
Trip free
Manual Actuator Type And Quantity:
1 toggle
Actuator Function:
Trip-reset
Actuator Position Designation:
At pole two
Auxiliary Switch Function And Quantity:
1 alarm
Adjustable Trip Setting Current Range Per Pole In Amps:
+2400.0/+6400.0 ac all locations
Switch Location And Position Designation:
Internal at pole one
Trip Release Ambient Tempurature Rating:
40.0 degrees celsius all locations
Switch Terminal Type:
Tab, solder lug
Switch Current Rating And Type In Amps:
6.0 ac and 0.25 dc
Switch Voltage Rating And Type In Volts:
240.0 ac and 250.0 dc
Frequency In Hertz:
50.0 all locations or 60.0 all locations
Terminal Type And Quantity:
6 compression
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A030a0