

View Online at <https://aerobasegroup.com/nsn/5925-01-238-5711>

**Body Style:**

Multipole-single actuator type

**Body Length:**

15.500 inches

**Body Width:**

8.250 inches

**Body Height:**

7.090 inches

**Case Material:**

Plastic

**Center To Center Distance Between Terminals Parallel To Length:**

9.120 inches

**Center To Center Distance Between Terminals Parallel To Width:**

2.750 inches

**Unthreaded Mounting Hole Diameter:**

0.250 inches

**Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:**

14.250 inches

**Switch Contact Arrangement:**

Single pole, double throw

**Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:**

2.750 inches

**Boss Height:**

0.250 inches

**Pole Quantity:**

2

**Mounting Facility Type And Quantity:**

4 unthreaded hole

**Features Provided:**

Adjustable trip release

**Maximum Continuous Load Current Rating Per Pole:**

1200.0 amperes ac all locations

**Operating Voltage Type And Rating Per Pole In Volts:**

600.0 ac all locations

**Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:**

22000.0 ac all locations

**Circuit Protection Type:**

Undervoltage all locations

**Trip Release Method:**

Thermal-magnetic all locations

**Trip Release Characteristic:**

Instantaneous all locations

**Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:**

125.0 all locations

**Reset Method:**

Manual

**Main Contact Tripping Mechanism Type:**

Trip free

**Manual Actuator Type And Quantity:**

1 toggle

**Actuator Function:**

Trip-reset

**Actuator Position Designation:**

At pole two

**Auxiliary Switch Function And Quantity:**

1 alarm

**Adjustable Trip Setting Current Range Per Pole In Amps:**

+2400.0/+6400.0 ac all locations

**Switch Location And Position Designation:**

Internal at pole one

**Trip Release Ambient Temperature Rating:**

40.0 degrees celsius all locations

**Switch Terminal Type:**

Tab, solder lug

**Switch Current Rating And Type In Amps:**

6.0 ac and 0.25 dc

**Switch Voltage Rating And Type In Volts:**

240.0 ac and 250.0 dc

**Frequency In Hertz:**

50.0 all locations or 60.0 all locations

**Terminal Type And Quantity:**

6 compression

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A030a0