NSN 5925-01-239-5928

Circuit Breaker Tripper - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5925-01-239-5928

view Offiline at https://defobasegroup.com/nsi//0325-01-253-0320
Body Style:
Rectangular dimensional envelope
Overall Length:
12.000 inches
Overall Height:
6.812 inches
Overall Width:
9.000 inches
Unthreaded Mounting Hole Diameter:
0.203 inches
Pole Quantity:
3
Mounting Facility Type And Quantity:
4 unthreaded hole
Storage Type:
General purpose warehouse
Features Provided:
Adjustable trip release
Maximum Continuous Load Current Rating Per Pole:
250.0 amperes ac all locations
Operating Voltage Type And Rating Per Pole In Volts:
500.0 ac all locations
Circuit Protection Type:
Overcurrent all locations
Trip Release Method:
Thermal-magnetic all locations
Trip Release Characteristic:
Instantaneous all locations
Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:
140.0 all locations
Manual Actuator Type And Quantity:
1 toggle
Actuator Function:
Trip-reset
Actuator Position Designation:
At pole two
Adjustable Trip Setting Current Range Per Pole In Amps:
+1500.0/+3000.0 ac all locations
Trip Release Ambient Tempurature Rating:
50.0 degrees celsius all locations

Feat

Criticality Code Justification:

NSN 5925-01-239-5928

Circuit Breaker Tripper - Page 2 of 2

Fiig: A030a0



Special Features:
Suffix a can only be safely used in conjunction with new style fuses
Frequency In Hertz:
60.0 all locations
Terminal Type And Quantity:
6 compression
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No