

View Online at <https://aerobasegroup.com/nsn/5925-01-240-2137>

Body Style:

Multipole-multiple actuator type

Body Length:

77.0 millimeters

Body Width:

15.6 millimeters

Body Height:

61.0 millimeters

Case Material:

Plastic

Center To Center Distance Between Terminals Parallel To Width:

7.8 millimeters

End Application:

2815-99-739-4949engine, diesel, model 16rp200m onboard 110 ft coast guard vessels

Pole Quantity:

2

Maximum Continuous Load Current Rating Per Pole:

16.0 amperes ac all locations

Operating Voltage Type And Rating Per Pole In Volts:

220.0 ac all locations

Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:

6000.0 ac all locations

Circuit Protection Type:

Overcurrent all locations

Trip Release Method:

Thermal-magnetic all locations

Trip Release Characteristic:

Instantaneous all locations

Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:

125.0 all locations

Reset Method:

Manual

Main Contact Tripping Mechanism Type:

Trip free

Manual Actuator Type And Quantity:

2 toggle

Actuator Function:

Trip-reset

Frequency In Hertz:

60.0 all locations

Terminal Type And Quantity:

4 compression

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A030a0