

View Online at <https://aerobasegroup.com/nsn/5925-01-240-7050>

**Body Style:**

Multipole-multiple actuator type

**Body Length:**

77.0 millimeters

**Body Width:**

15.6 millimeters

**Body Height:**

61.0 millimeters

**Case Material:**

Plastic

**Center To Center Distance Between Terminals Parallel To Width:**

7.8 millimeters

**End Application:**

2815-99-739-4949engine, diesel, model 16rp200m onboard 110 ft coast guard vessels

**Pole Quantity:**

2

**Maximum Continuous Load Current Rating Per Pole:**

25.0 amperes ac all locations

**Operating Voltage Type And Rating Per Pole In Volts:**

220.0 ac all locations

**Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:**

6000.0 ac all locations

**Circuit Protection Type:**

Overcurrent all locations

**Trip Release Method:**

Thermal-magnetic all locations

**Trip Release Characteristic:**

Instantaneous all locations

**Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:**

125.0 all locations

**Reset Method:**

Manual

**Main Contact Tripping Mechanism Type:**

Trip free

**Manual Actuator Type And Quantity:**

2 toggle

**Actuator Function:**

Trip-reset

**Frequency In Hertz:**

60.0 all locations

**Terminal Type And Quantity:**

4 compression

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A030a0