

View Online at <https://aerobasegroup.com/nsn/5925-01-240-8035>

Body Style:

Multipole-single actuator type

Bushing Length:

0.468 inches

Body Length:

1.375 inches

Body Width:

1.360 inches

Case Material:

Plastic

Center To Center Distance Between Terminals Parallel To Length:

1.125 inches

Center To Center Distance Between Terminals Parallel To Width:

0.680 inches

Mounting Surface To Terminal End Distance:

1.555 inches

Pole Quantity:

2

Arc Quenching Method:

Magnetic blowout

Mounting Facility Type And Quantity:

1 threaded bushing w/panel seal

Storage Type:

General purpose warehouse

Thready Qty Per Inch (tpi):

32

Maximum Continuous Load Current Rating Per Pole:

12.5 amperes ac all locations

Operating Voltage Type And Rating Per Pole In Volts:

250.0 ac all locations

Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:

1000.0 ac all locations

Circuit Protection Type:

Overcurrent all locations

Trip Release Method:

Magnetic all locations

Trip Release Characteristic:

Time delay all locations

Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:

125.0 all locations

Reset Method:

Manual

Main Contact Tripping Mechanism Type:

Trip free

Manual Actuator Type And Quantity:

1 toggle

Actuator Function:

Trip-reset

Actuator Position Designation:

Between pole one and two

Internal Trip Release Configuration:

Series trip all locations

Thread Size:

0.250 inches

Trip Delay Time In Seconds Per Rated Continuous Current:

1.000 at 200 pct all locations and 15.000 at 200 pct all locations

Inclosure Protection Type For Which Designed:

Fungus resistant

Frequency In Hertz:

50.0 all locations or 60.0 all locations

Unpackaged Unit Weight:

2.400 ounces

Thread Series Designator:

Un

Terminal Type And Quantity:

4 quick disconnect, male

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiiig:

A030a0