

View Online at <https://aerobasegroup.com/nsn/5925-01-240-9181>

Body Style:

Multipole-multiple actuator type

Bushing Length:

0.100 inches

Body Length:

1.930 inches

Body Width:

1.400 inches

Case Material:

Plastic

Center To Center Distance Between Terminals Parallel To Length:

0.960 inches

Center To Center Distance Between Terminals Parallel To Width:

0.700 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

1.620 inches

Mounting Surface To Terminal End Distance:

1.480 inches

Pole Quantity:

2

Mounting Facility Type And Quantity:

2 threaded hole

Storage Type:

General purpose warehouse

Thready Qty Per Inch (tpi):

32

Maximum Continuous Load Current Rating Per Pole:

15.0 amperes ac all locations and 15.0 amperes dc all locations

Operating Voltage Type And Rating Per Pole In Volts:

250.0 ac all locations and 28.0 dc all locations

Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:

150.0 ac all locations and 150.0 dc all locations

Circuit Protection Type:

Overcurrent all locations

Trip Release Method:

Thermal all locations

Trip Release Characteristic:

Time delay all locations

Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:

125.0 all locations

Reset Method:

Manual

Main Contact Tripping Mechanism Type:

Trip free

Manual Actuator Type And Quantity:

1 toggle

Actuator Function:

Trip-reset

Actuator Position Designation:

Between pole one and two

Internal Trip Release Configuration:

Series trip all locations

Thread Size:

0.138 inches

Trip Delay Time In Seconds Per Rated Continuous Current:

3.000 at 300 pct all locations and 12.000 at 300 pct all locations

Inclosure Protection Type For Which Designed:

Fungus resistant

Trip Release Ambient Temperature Rating:

70.0 degrees fahrenheit all locations

Frequency In Hertz:

50.0 all locations or 60.0 all locations

Thread Series Designator:

Unc

Terminal Type And Quantity:

4 quick disconnect, male

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A030a0