

View Online at <https://aerobasegroup.com/nsn/5925-01-241-4589>

**Body Length:**

2.490 inches

**Case Material:**

Plastic

**Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:**

2.060 inches

**Boss Height:**

0.150 inches

**Pole Quantity:**

3

**Mounting Facility Type And Quantity:**

2 threaded hole

**Thready Qty Per Inch (tpi):**

32

**Maximum Continuous Load Current Rating Per Pole:**

2.0 amperes ac all locations

**Operating Voltage Type And Rating Per Pole In Volts:**

480.0 ac all locations

**Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:**

5000.0 ac all locations

**Circuit Protection Type:**

Overcurrent all locations

**Trip Release Method:**

Magnetic all locations

**Trip Release Characteristic:**

Time delay all locations

**Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:**

125.0 all locations

**Reset Method:**

Automatic

**Main Contact Tripping Mechanism Type:**

Trip free

**Manual Actuator Type And Quantity:**

3 toggle

**Actuator Function:**

Trip-reset

**Thread Size:**

0.138 inches

**Trip Delay Time In Seconds Per Rated Continuous Current:**

0.700 at 125 pct all locations and 10.000 at 125 pct all locations

**Inclosure Protection Type For Which Designed:**

Dustproof and fungus resistant and salt spray proof and water resistant

**Special Features:**

1 hex nut 2 flat washers provided with each term

**Frequency In Hertz:**

50.0 all locations or 60.0 all locations

**Terminal Type And Quantity:**

2 threaded stud

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A030a0