# NSN 5925-01-242-2688

Circuit Breaker - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5925-01-242-2688

#### **Body Style:**

Multipole-multiple actuator type

#### **Body Length:**

4.750 inches

## Body Width:

3.108 inches

#### **Case Material:**

Plastic

#### Center To Center Distance Between Terminals Parallel To Length:

3.550 inches

#### Center To Center Distance Between Terminals Parallel To Width:

#### 1.026 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

#### 2.750 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

## 1.026 inches

Boss Height:

0.220 inches

# Mounting Surface To Terminal End Distance:

3.375 inches

#### **Pole Quantity:**

3

#### Arc Quenching Method:

Magnetic blowout

#### Mounting Facility Type And Quantity:

6 threaded hole

#### Storage Type:

General purpose warehouse

#### **Features Provided:**

High inrush protection

#### Thready Qty Per Inch (tpi):

32

## Maximum Continuous Load Current Rating Per Pole:

4.5 amperes ac all locations

## Operating Voltage Type And Rating Per Pole In Volts:

240.0 ac all locations

## Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:

5000.0 ac all locations

## **Circuit Protection Type:**

Overcurrent all locations

### Trip Release Method:

Magnetic-hydraulic all locations

# NSN 5925-01-242-2688

Circuit Breaker - Page 2 of 2



**Trip Release Characteristic:** Time delay all locations Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent: 125.0 all locations **Reset Method:** Manual Main Contact Tripping Mechanism Type: Trip free Manual Actuator Type And Quantity: 3 toggle Actuator Function: Trip-reset **Actuator Position Designation:** At each pole **External Actuator Linkage Arrangement:** One, two, and three linked Internal Trip Release Configuration: Relay trip all locations **Thread Size:** 0.138 inches Trip Delay Time In Seconds Per Rated Continuous Current: 40.000 at 200 pct all locations and 200.000 at 200 pct all locations **Inclosure Protection Type For Which Designed:** Fungus resistant **Frequency In Hertz:** 50.0 all locations or 60.0 all locations **Unpackaged Unit Weight:** 2.000 pounds **Thread Series Designator:** Unc **Terminal Type And Quantity:** 12 threaded stud Shelf Life: N/a Unit Of Measure: ---**Demilitarization:** No Fiig: A030a0