NSN 5925-01-243-2895

Circuit Breaker - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5925-01-243-2895

Thread Pitch Diameters:

+2.99/+3.08 millimeters

Body Style:

Multipole-single actuator type

Body Length:

2.000 inches

Body Width:

2.265 inches

Case Material:

Plastic

Center To Center Distance Between Terminals Parallel To Length:

1.530 inches

Center To Center Distance Between Terminals Parallel To Width:

0.750 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

1.660 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

0.750 inches

Fragility Factor:

Moderately rugged

Boss Height:

0.130 inches

Mounting Surface To Terminal End Distance:

2.000 inches

Pole Quantity:

3

Arc Quenching Method:

Magnetic blowout

Mounting Facility Type And Quantity:

6 threaded hole

Storage Type:

General purpose warehouse

Special Handling Feature:

Magnetic

Maximum Continuous Load Current Rating Per Pole:

1.0 amperes ac all locations

Operating Voltage Type And Rating Per Pole In Volts:

240.0 ac all locations

Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:

2100.0 ac all locations

Circuit Protection Type:

Overcurrent all locations

NSN 5925-01-243-2895

Circuit Breaker - Page 2 of 2



Trip Release Method: Magnetic-hydraulic all locations **Trip Release Characteristic:** Time delay all locations Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent: 115.0 all locations **Reset Method:** Manual Main Contact Tripping Mechanism Type: Trip free Manual Actuator Type And Quantity: 1 toggle **Actuator Function:** Trip-reset **Actuator Position Designation:** At pole two Internal Trip Release Configuration: Series trip all locations **Thread Size:** 3.5 millimeters Trip Delay Time In Seconds Per Rated Continuous Current: 2.200 at 200 pct all locations and 25.000 at 200 pct all locations **Inclosure Protection Type For Which Designed:** Hermetically sealed and shock resistant and vibration resistant **Special Features:** Actuator black without markings **Frequency In Hertz:** 400.0 all locations **Unpackaged Unit Weight:** 6.600 ounces **Thread Series Designator:** lso m **Terminal Type And Quantity:** 6 tab w/screw Shelf Life: N/a Unit Of Measure: **Demilitarization:** No Fiig: A030a0