

View Online at <https://aerobasegroup.com/nsn/5925-01-243-3772>

Body Style:

Multipole-multiple actuator type

Body Length:

9.500 inches

Body Width:

4.500 inches

Body Height:

4.000 inches

Case Material:

Plastic

Center To Center Distance Between Terminals Parallel To Length:

8.000 inches

Center To Center Distance Between Terminals Parallel To Width:

1.750 inches

Unthreaded Mounting Hole Diameter:

0.281 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

7.500 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

1.750 inches

End Application:

Used on power panel aboard 210 ft wmec "a" and "b" class coast guard vessels

Boss Height:

0.250 inches

Pole Quantity:

3

Mounting Facility Type And Quantity:

4 unthreaded hole

Cubic Measure:

0.094 cubic feet

Maximum Continuous Load Current Rating Per Pole:

175.0 amperes ac all locations

Operating Voltage Type And Rating Per Pole In Volts:

600.0 ac all locations

Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:

175.0 ac all locations

Circuit Protection Type:

Overcurrent all locations

Trip Release Method:

Thermal-magnetic all locations

Trip Release Characteristic:

Instantaneous all locations

Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:

125.0 all locations

Reset Method:

Manual

Main Contact Tripping Mechanism Type:

Trip free

Trip Release Duty Cycle:

Intermittent all locations

Trip Release Ambient Temperature Rating:

50.0 degrees celsius all locations

Frequency In Hertz:

60.0 all locations

Unpackaged Unit Weight:

12.000 pounds

Terminal Type And Quantity:

6 compression

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A030a0