

View Online at <https://aerobasegroup.com/nsn/5925-01-243-3773>

**Body Style:**

Multipole-multiple actuator type

**Body Length:**

9.500 inches

**Body Width:**

4.500 inches

**Body Height:**

4.000 inches

**Case Material:**

Plastic

**Center To Center Distance Between Terminals Parallel To Length:**

8.000 inches

**Center To Center Distance Between Terminals Parallel To Width:**

1.750 inches

**Unthreaded Mounting Hole Diameter:**

0.281 inches

**Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:**

7.500 inches

**Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:**

1.750 inches

**End Application:**

Power panel aboard 210 ft wmec "a" and "b" class coast guard vessels

**Boss Height:**

0.250 inches

**Pole Quantity:**

3

**Mounting Facility Type And Quantity:**

4 unthreaded hole

**Cubic Measure:**

0.094 cubic feet

**Maximum Continuous Load Current Rating Per Pole:**

150.0 amperes ac all locations

**Operating Voltage Type And Rating Per Pole In Volts:**

600.0 ac all locations

**Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:**

150.0 ac all locations

**Circuit Protection Type:**

Overcurrent all locations

**Trip Release Method:**

Thermal-magnetic all locations

**Trip Release Characteristic:**

Instantaneous all locations

**Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:**

125.0 all locations

**Reset Method:**

Manual

**Main Contact Tripping Mechanism Type:**

Trip free

**Trip Release Duty Cycle:**

Intermittent all locations

**Trip Release Ambient Temperature Rating:**

50.0 degrees celsius all locations

**Frequency In Hertz:**

60.0 all locations

**Unpackaged Unit Weight:**

12.000 pounds

**Terminal Type And Quantity:**

6 compression

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A030a0