

View Online at <https://aerobasegroup.com/nsn/5925-01-245-1409>

**Body Style:**

Single pole type

**Body Length:**

2.000 inches

**Body Width:**

0.920 inches

**Body Height:**

1.770 inches

**Case Material:**

Plastic

**Boss Height:**

0.125 inches

**Pole Quantity:**

1

**Arc Quenching Method:**

Magnetic blowout

**Mounting Facility Type And Quantity:**

2 clip

**Storage Type:**

General purpose warehouse

**Features Provided:**

High inrush protection

**Maximum Continuous Load Current Rating Per Pole:**

10.0 amperes ac single location

**Operating Voltage Type And Rating Per Pole In Volts:**

250.0 ac single location

**Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:**

1000.0 ac single location

**Circuit Protection Type:**

Overcurrent single location

**Trip Release Method:**

Magnetic single location

**Trip Release Characteristic:**

Time delay single location

**Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:**

125.0 single location

**Reset Method:**

Manual

**Main Contact Tripping Mechanism Type:**

Trip free

**Manual Actuator Type And Quantity:**

1 toggle

**Actuator Function:**

Trip-reset

**Actuator Position Designation:**

At pole one

**Internal Trip Release Configuration:**

Series trip single location

**Trip Delay Time In Seconds Per Rated Continuous Current:**

0.200 at 200 pct single location and 1.700 at 200 pct single location

**Inclosure Protection Type For Which Designed:**

Fungus resistant

**Special Features:**

Light on handle

**Frequency In Hertz:**

50.0 single location or 60.0 single location

**Unpackaged Unit Weight:**

1.800 ounces

**Terminal Type And Quantity:**

2 quick disconnect, male

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A030a0