## NSN 5925-01-245-2000

Circuit Breaker - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5925-01-245-2000 **Body Style:** Single pole type **Bushing Length:** 0.500 inches **Body Length:** 2.000 inches **Body Width:** 0.750 inches **Case Material: Plastic Center To Center Distance Between Terminals Parallel To Length:** 1.530 inches **Switch Contact Arrangement:** Single pole, double throw **End Application:** 1430-01-131-5373 **Mounting Surface To Terminal End Distance:** 2.232 inches **Pole Quantity: Mounting Facility Type And Quantity:** 1 threaded bushing w/panel seal Storage Type: General purpose warehouse Thready Qty Per Inch (tpi): 32 **Maximum Continuous Load Current Rating Per Pole:** 7.5 amperes ac single location **Operating Voltage Type And Rating Per Pole In Volts:** 250.0 ac single location Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps: 1000.0 ac single location **Circuit Protection Type:** Overcurrent single location **Trip Release Method:** Magnetic single location **Trip Release Characteristic:** Time delay single location **Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:** 

150.0 single location

**Reset Method:** 

Manual

## NSN 5925-01-245-2000

Circuit Breaker - Page 2 of 2



Main Contact Tripping Mechanism Type:
Trip free
Manual Actuator Type And Quantity:
1 toggle
Actuator Function:
Trip-reset
Actuator Position Designation:
At pole one
Auxiliary Switch Function And Quantity:
1 alarm
Internal Trip Release Configuration:
Series trip single location
Thread Size:
0.500 inches
Switch Location And Position Designation:
Internal at pole one
Trip Delay Time In Seconds Per Rated Continuous Current:
0.150 at 200 pct single location and 1.900 at 200 pct single location
Inclosure Protection Type For Which Designed:
Explosion resistant and moisture resistant
Switch Terminal Type:
Tab, solder lug
Switch Current Rating And Type In Amps:
10.0 ac and 5.0 dc
Switch Voltage Rating And Type In Volts:
250.0 ac and 30.0 dc
Frequency In Hertz:
400.0 single location
Unpackaged Unit Weight:
2.000 ounces
Thread Series Designator:
Un
Terminal Type And Quantity:
2 tab w/screw
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Filg:
A030a0